

Model	Description: Thermostats
Programmable Thermostats	
TB7220U1012/U	Commercial Pro Soft Button, 24 Vac 2 heat 2 cool or 3 heat 2 cool
Remote Temperature Sensors	
C7189U1005/U	NTC 10K indoor temperature sensor for TB7000 & TB8000
C7089U1006/U	NTC 10K outdoor temperature sensor for TB7000 & TB8000
Zone Pro Thermostats	
TB6980A1007/U	ZONEPRO 24V FLOATING VAV STAT SINGLE OUT
TB6980B1006/U	ZONEPRO 24V FLOATING VAV STAT MULTIPLE OUT
TB7980A1006/U	ZONEPRO TEMP CONTROLLER MOD 0-10V OUTPUT
TB7980B1005/U	ZONEPRO TEMP CONTROLLER MOD 0-10V PLUS 2ND 0-10V TRIAC OUTPUT
FCU Thermostats Non Programmable (Halo on / off)	
T6861H2WG/U	2 or 4 pipe FCU thermostat 1 heat & 1cool horizontal mount Blue LCD display
T6861V2WG/U	2 or 4 pipe FCU thermostat 1 heat & 1cool vertical mount Blue LCD display
FCU Thermostats Non Programmable (Halo modulating)	
T6865H2WB	2/4 pipe FCU thermostat 1 heat & 1cool horizontal mount Blue LCD display
T6865H2WB-R	2/4 pipe FCU thermostat 1 heat & 1cool horizontal mount Blue LCD display, Remote Sensor
T6865H2WG	2/4 pipe FCU thermostat 1 heat & 1cool horizontal mount Green LCD display
T6865H2WG-R	2/4 pipe FCU thermostat 1 heat & 1cool horizontal mount Green LCD display, Rem. Sensor
Industrial Space thermostat 1 / 2 stages	
T6120A1005	Thermostat for heating, cooling & ventilation 0 - 60°C SPDT 250Vac 10A IP54
T6120B1003	Thermostat for heating, cooling & ventilation -30 - +30°C SPDT 250Vac 15A IP54
Thermostat corrosion resistive for lift motor rooms, storage areas, swimming pools etc	
T631C1160/U	TStat heating, cooling & ventilation 20° to 60°C, 230Vac, 5A resistive, 3.7 A inductive
Single stage frost protection thermostat for down stream air heaters, electrical heating systems	
FT6960-18	FPT IP65, -20 to 55°C, SPDT 24-250Vac, 15A res 8A ind, capillary length 1.8m, manual reset
FT6960-30	FPT IP65, -20 to 55°C, SPDT 24-250Vac, 15A res 8A ind, capillary length 3m, manual reset
FT6960-60	FPT IP65, -20 to 55°C, SPDT 24-250Vac, 15A res 8A ind, capillary length 6m, manual reset
FT6961-18	FPT IP65, -20 to 55°C, SPDT 24-250Vac, 15A res 8A ind, capillary length 1.8m, auto reset
FT6961-30	FPT IP65, -20 to 55°C, SPDT 24-250Vac, 15A res 8A ind, capillary length 3m, auto reset
FT6961-60	FPT IP65, -20 to 55°C, SPDT 24-250Vac, 15A res 8A ind, capillary length 6m, auto reset
Safety Limiting thermostats with manual reset IP54	

Model	Description: Thermostats
STB1	SPT with well, 60 - 130°C, SPST 230Vac, 10A, immersion depth 150mm, 1/2" dia
STW1	SPT with well, 20 - 150°C, SPDT 230Vac, 10A, immersion depth 150mm, 1/2" dia
T4NST	Steel well R1/2" x 150mm
Safety limiting thermostat with setpoint knob & shut off IP54 immersion depth 150mm	
STB+TR	SPT well. Safety temp ctrl with hi temp shutoff, 30-110°C, SPDT/SPST 230Vac, 10A
T5NST	Steel Well R1/2" X 150mm
Safety Limiting Thermostat with automatic reset IP54 immersion depth 100mm.	
TWP1	Sealing pipe thermostat with well. Monitors steam, hot water & district heating system
T4NST	Steel well R1/2" X 150mm
Accessories	Remote Temperature Sensors
C7189U1005/U	NTC 10K indoor temperature sensor for TB7000 & TB8000
C7089U1006/U	NTC 10K outdoor temperature sensor for TB7000 & TB8000
Interface Module	
R4611G2010	Low Voltage to line voltage interface for 24 Vac thermostats LC = AUD 10.30
Lockable Thermostat Protective Covers	
TG510A1001/U	TSTAT GUARD SMALL CLEAR PLAST COVER + RING BASE
TG511A1000/U	TSTAT GUARD MED CLEAR PLAST COVER + RING BASE
TG512A1009	TSTAT GUARD LARGE CLEAR PLAST COVER + RINGBASE
BACnet Communicating Thermostats	
TB7200C5014B/U	2 FLT ON/OFF 1 AUX ZONE MOD W RH BNET
TB7200C5514B/U	2 FLT ON/OFF 1 AUX ZONE OCC MOD RH BNET
TB7200F5014B/U	2 0-10VDC 1 AUX ZONE MOD W RH BNET
TB7200F5514B/U	2 0-10VDC 1 AUX ZONE OCC MOD W RH BNET
TB7300A5014B/U	2 DIG 1 AUX FAN COIL BNET
TB7300A5514B/U	2 DIG 1 AUX FAN COIL W OCC BNET
TB7300C5014B/U	2 FLT 1 AUX FAN COIL BNET
TB7300C5514B/U	2 FLT 1 AUX FAN COIL W OCC BNET
TB7300F5014B/U	2 ANALOG 1 AUX FAN COIL BNET
TB7300F5514B/U	2 ANALOG 1 AUX FAN COIL W OCC BNET
TB7305A5014B/U	2 DIG 1 AUX FAN COIL BNET HOTEL
TB7305A5514B/U	2 DIG 1 AUX FAN COIL W OCC BNET HOTEL

Model	Description: Thermostats
TB7305C5014B/U	2 FLT 1 AUX FAN COIL BNET HOTEL
TB7305C5514B/U	2 FLT 1 AUX FAN COIL W OCC BNET HOTEL
TB7305F5014B/U	2 ANA 1 AUX FAN COIL BNET HOTEL
TB7305F5514B/U	2 ANA 1 AUX FAN COIL W OCC BNET HOTEL
TB7350C5014B/U	2 FLT 1 AUX FAN COIL W RH BNET
TB7350C5514B/U	2 FLT 1 AUX FAN COIL W OCC and RH BNET
TB7350F5014B/U	2 ANA 1 AUX FAN COIL W RH BNET
TB7350F5514B/U	2 ANA 1 AUX FAN COIL W OCC RH BNET
TB7355C5014B/U	2 FLT 1 AUX FAN COIL W RH BNET HOTEL
TB7355C5514B/U	2 FLT 1 AUX FAN COIL OCC RH BNET HOTEL
TB7355F5014B/U	2 ANA 1 AUX FAN COIL W RH BNET HOTEL
TB7355F5514B/U	2 ANA 1 AUX FAN COIL OCC RH BNET HOTEL
TB7600A5014B/U	1H/1C RTU BNET
TB7600A5514B/U	1H/1C RTU W/ OCC BNET
TB7600B5014B/U	2H/2C RTU BNET
TB7600B5514B/U	2H/2C RTU W/ OCC BNET
TB7600H5014B/U	3H/2C HEAT PUMP BNET
TB7600H5514B/U	3H/2C HEAT PUMP W/ OCC BNET
TB7605B5014B/U	2H/2C RTU W/ ECON BNET
TB7605B5514B/U	2H/2C RTU W/ ECON and OCC BNET
TB7607B5014B/U	2H/2C RTU W/ HUMID BNET
TB7607B5514B/U	2H/2C RTU W/ HUMID and OCC BNET
TB7652A5014B/U	1H/1C RTU W/ SCHED BNET
TB7652A5514B/U	1H/1C RTU W/ SCHED and OCC BNET
TB7652B5014B/U	2H/2C RTU W/ SCHED BNET
TB7652B5514B/U	2H/2C RTU W/ SCHED and OCC BNET
TB7652H5014B/U	3H/2C HEAT PUMP W/ SCHED BNET
TB7652H5514B/U	3H/2C HEAT PUMP W/ SCHED and OCC BNET
TB7656B5014B/U	2H/2C RTU W/ ECON and SCHED BNET
TB7656B5514B/U	2H/2C RTU W/ ECON, SCHED and OCC BNET
TB7657B5014B/U	2H/2C RTU W/ HUMID and SCHED BNET

Model	Description: Thermostats
TB7657B5514B/U	2H/2C RTU W/ HUMID, SCHED and OCC BNET