

FX - DDC Field Devices

Type	Part Number	Description
BCM	CN-BRTR-0	BACnet IP to MS/TP Router, 1 MS/TP Trunk, upto 100 FX-PC or 64 devices
	CH-BCM100-0	Building Control Manager Workstation Software, 3,000 Objects, New Project
	CH-BCM200-0	Building Control Manager Workstation Software, 10,000 Objects, New Project
	CN-BIG1970-0	BACnet IP to Modbus IP or Remote Terminal Unit (RTU) Gateway, 1 RTU Trunk
DDC FX-PC, MSTP	FX-DIS1710-0	Local display for FX-PCG and FX-PCV
	FX-PCG1611-1	Controller, 10 IOs, 2 UI, 1 BI, 3 BO, and 4 CO
	FX-PCG1621-1	Controller, 10 IOs, 2 UI, 1 BI, 3 BO, and 4 CO, Display
	FX-PCG2611-0	Controller, 17 IOs, 6 UI, 2 BI, 3 BO, 2 AO, 4 CO
	FX-PCG2621-0	Controller, 17 IOs, 6 UI, 2 BI, 3 BO, 2 AO, 4 CO, Display
	FX-PCA2611-0	Controller, 17 IOs, 6 UI, 2 BI, 3 BO, 2 AO, 4 CO, 24vAC, time
	FX-PCA2612-1	Controller, 18 IOs, 5 UI, 4 BI, 4 CO, 5 RO (relay, 2 SPDT+3 SPST), 24vAC, time
	FX-PCA2612-2	Controller, 18 IOs, 5 UI, 4 BI, 4 CO, 5 RO (relay, 2 SPDT+3 SPST), 240vAC, time
	FX-PCA3611-0A	Controller, 26 IOs, 8 UI, 6 BI, 6 BO, 6 AO; SA+FC Bus, 24vAC, time
	FX-PCX1711-0	Expansion 4 I/O Module: 4 BI
	FX-PCX2711-0	Expansion 6 I/O Module: 2 UI, 2 UO, 2 RO
	FX-PCX2721-0	Expansion 10 I/O Module: 8 UI, 2 AO
	FX-PCX3711-0	Expansion 12 I/O Module: 4 UI, 4 UO, 4 RO
	FX-PCX3721-0	Expansion 16 I/O Module: 16 BI
	FX-PCX3731-0A	Expansion 16 I/O Module: 8 BI, 8 BO
	FX-PCX4711-0	Expansion 17 I/O Module: 6 UI, 2 BI, 3 BO, 2 AO, 4 CO
	VAV & FCU	FX-PCV1628-0
FX-PCV1626-0		VAV Controller, W/actuator, No DP. 3 UI, 3 BO, 2 CO; 24 VAC; FC/SA Bus (SQ)
FX-PCV1656-0		VAV Controller, W/actuator, No DP. 3 UI, 3 BO, 2 CO; 24 VAC; FC/SA Bus, Valve linkage (SQ)
TUC0311-2		240VAC N2/BACNET
FX-PCV1615-0		VMA, +3UI, 2BO, 6 pin SA bus for NS sensor
FX-PCV1617-0		VMA, +3UI, 2BO, 8 pin SA bus for Analog sensor
FX-PCV1630-0		VMA, +3UI, 3BO, 2CO, 6 pin SA bus for NS sensor
FX-PCV1632-0		VMA, +3UI, 3BO, 2CO, 8 pin SA bus for NS/Analog sensor
FX-PCV1832-0		VMA, +3UI, 3BO, 2CO, 8 pin SA bus for Analog sensor, N2
FX-ATV7003-0		Handheld VAV Balancing Tool
FX-BTCVT-1		Bluetooth® Commissioning Converter
TE730-29C-0		Room Sensor Pt1000, Setpoint Adjustment
TE730-39C-0		Room Sensor Pt1000, Setpoint Adjustment and Occupy
NS-ATN7003-0		Network room sensor for VAV
NS-ATA7002-0A		Network room sensor for VAV air, Display and setpoint Adj
JCA-TE88-1		Room Sensor 10kNTC
Tools		JCA-PES-22
	JCA-PES-23	Engineering - Software (DDC programming, data base)
	JCA-PES-24	Engineering - Graphics (home page, floor plan)
	JCA-PES-25	Engineering - Conversion (Convert old system to new system)
	JCA-PES-26	Engineering - remote commissioning support (home page, floor plan)
	FX-PCT-0	FX-PCT Programming tool, New
	JCA-RP485	RS-485 bus repeater (MS/TP or N2 protocol) – 230VAC power supply
	MS-BACEOL-0	End-of-Line Terminator Module
	TL-BRTRP-0	Portable BACnet/IP to MS/TP router for FX, FX-PC, FEC, etc.
	FX-BTCVT-1	Bluetooth® Commissioning Converter
	TL-MAP1810-0P	Portable version of MAP Gateway
	TL-MAP1810-0S	Stationary version of MAP Gateway w/power supply+mounting cradle
	JCA-DCBL3725SB	Cable (Brown PVC), 3 Core shielded, AI/AO, 500 meter roll
	JCA-DCBL3725SV	Cable (Violet PVC), 3 Core shielded, MSTP bus, 500meter roll

FX - DDC Field Devices

Type	Part Number	Description
	JCA-LSHF3725SV	Cable (Violet green building), 3 Core shielded, MSTP bus, 500meter roll