



Sensor - Pressure

Application	Part Number	Description
DP Air	DPT-2015-1	DP Air 0-1.5 DIFF PRESS. TO
	DP2500-R8	DP Air: 8 ranges, 0-100,250,1000,1500,2000,2500, +/-100,4-20mA/0-10vDC, 24v, kit (tube, tip, screw)
	DP2500-R8-01	Same as DP2500-R8, 46 bulk pack, no kit
	DP2500-R8-AZ	DP Air: 8 ranges, 0-100,250,1000,1500,2000,2500, +/-100,4-20mA/0-10vDC, 24v, Autozero, kit
	DP2500-R8-AZ-01	Same as DP2500-R8-AZ, 46 bulk pack, no kit
	DP2500-R8-D	DP Air 8 ranges, 0-100,250,1000,1500,2000,2500, +/-100;4-20mA/0-10vDC, 24v, Display, kit
	DP2500-R8-AZ-D	DP Air: 8 ranges, 0-100,250,1000,1500,2000,2500, +/-100,4-20mA/0-10vDC, 24v, Display, Autozero,
	DP0250-R8-AZ	DP Air: 8 ranges, 0-25,50,100,250, +/- 25, 50, 100,150,4-20mA/0-10vDC, 24v, AutoZero ,kit
	DP0250-R8-AZ-01	Same as DP0250-R8-AZ, 46 bulk pack, no kit
	DP0250-R8-AZ-D	DP Air: 8 ranges, 0-25,50,100,250, +/- 25, 50, 100,150,4-20mA/0-10vDC, 24v, AutoZero, Display, kit
DP Water	JCA-PR282-31B	DP Water, 0-20 psi/0-10vDC, 24 vAC Power
	JCA-PR282-34B	DP Water, 0-100 psi/0-10vDC, 24 vAC Power
DP Air	P32AC-2C	DP Air, 0.012/1.24 Kpa, w/FTG18A-600R
	P32AF-2C	DP Air, 0.006/1.24 Kpa, w/FTG18A-600R
	P32AC-2D	DP Air, 0.012/1.24KPA, Bulk pack 30 pcs, w FTG18A-600R
	P233A-4-PAD	DP Air, 50 to 400 Pa, bulk pack 70 pcs, no accessory
DP Water	P74EA-8C	DP Water, Adjustable range 14/180Kpa. Max 1024Kpa
	P74FA-9C	DP Water, Adjustable range 50/400Kpa, Max 1024Kpa
	P74BA-1C	DP Water, Adjustable range 55/483Kpa, Max 2241Kpa.
	P74JA-2C	DP water, floating
Refrigerant	P499VCS-401C	Pres sensor, -100/800Kpa, 0-10vDC, 1/4 SAE F, 2m Lead
	P499VCS-404C	Pres sensor, 0/3000Kpa, 0-10vDC, 1/4 SAE F, 2m lead
	P499VCS-405C	Pres sensor, 0/5000Kpa, 0-10vDC, 1/4 SAE F, 2m lead
Accessory	T00199	Kit, 2m tube (φ4mm forφ5mm connector, DP2500/P233), 2 static pressure tip, 2 screw
	GMT008N600R	Kit,  (φ4mm forφ5mm connector, DP2500/P233), 2 grommets (drilling hole 16mm)
	FTG18A-600R	Kit,  tip(4" with mounting flange), 2 brass barb fittings (1/4"=6mm), 2 screws, 1 gasket
	028G00027A025	Pilot Tube, 304 m/roll, (φ4.3mm for 1/4" brass barb fitting, VMA) Red
	028G00027A026	Pilot Tube, 304 m/roll, (φ4.3mm for 1/4" brass barb fitting, VMA) Black
	A-480	Static pressure tip, 3", plastic, L=80+20mm, D=φ5mm, mounting φ25mm
	A-489	Static pressure tip, 4", SS,
Pneumatic	EP-8000-2	Electro-Pneumatic Transducer, 0.5-9.5 vDC/ 0.5-19 Psig