

**PICV (Pressure Independent Balancing Valve)+ Actuator**

Type	Valve Body						Valve Actuator		Linkage Code	DAT Actuator Option
	Code	Description	Size	ΔP	Connection	Flow Max	Code	Description		
			mm	kPa						
					l/s					
Modulating 0-10 Application	VP100AAA	PICV, 15mm, 0.04l/s, Adj., w/act.0-10vDC, 24vAC	15	20-400	Female BSPP	0.04	VA-7091-21	0-10vDC, 24vAC	0550390101	VA-7071-21
	VP100AAE	PICV, 15mm, 0.17l/s, Adj., w/act.0-10vDC, 24vAC	15	20-400	Female BSPP	0.17	VA-7091-21	0-10vDC, 24vAC	0550390101	VA-7071-21
	VP100AAG	PICV, 15mm, 0.22l/s, Adj., w/act.0-10vDC, 24vAC	15	20-400	Female BSPP	0.22	VA-7091-21	0-10vDC, 24vAC	0550390101	VA-7071-21
	VP100BAJ	PICV, 20mm, 0.28l/s, Adj., w/act.0-10vDC, 24vAC	20	25-400	Female BSPP	0.28	VA-7091-21	0-10vDC, 24vAC	0550390101	VA-7071-21
	VP100BAN	PICV, 20mm, 0.42l/s, Adj., w/act.0-10vDC, 24vAC	20	25-400	Female BSPP	0.42	VA-7091-21	0-10vDC, 24vAC	0550390101	VA-7071-21
	VP100CAU	PICV, 25mm, 0.61l/s, Adj., w/act.0-10vDC, 24vAC, Elec	25	25-400	Female BSPP	0.61	VA-7482-3001	0-10vDC, 24vAC, Elec	0A748X	
	VP100CAW	PICV, 25mm, 0.75l/s, Adj., w/act.0-10vDC, 24vAC, Elec	25	25-400	Female BSPP	0.75	VA-7482-3001	0-10vDC, 24vAC, Elec	0A748X	
	VP100DAW	PICV, 32mm, 0.75l/s, Adj., w/act.0-10vDC, 24vAC, Elec	32	25-400	Female BSPP	0.75	VA-7482-3001	0-10vDC, 24vAC, Elec	0A748X	
	VP100DAY	PICV, 32mm, 0.83l/s, Adj., w/act.0-10vDC, 24vAC, Elec	32	25-400	Female BSPP	0.83	VA-7482-3001	0-10vDC, 24vAC, Elec	0A748X	
	VPA032-C	PICV, 32mm, 0.96l/s, Adj., w/act.0-10vDC, 24vAC, Elec	32	50-400	Female ISO7/1(Rp)	0.96	VAP500-24-C	0-10vDC, 24vAC, Elec		
	VPA040-C	PICV, 40mm, 1.64l/s, Adj., w/act.0-10vDC, 24vAC, Elec	40	50-400	Female ISO7/1(Rp)	1.64	VAP500-24-C	0-10vDC, 24vAC, Elec		
	VPA050B-C	PICV, 50mm, 2.19l/s, Adj., w/act.0-10vDC, 24vAC, Elec	50	35-400	Flange ISO7005-2	2.19	VAP500-24-C	0-10vDC, 24vAC, Elec		
	VP101EBD	PICV, 50mm, 3.06l/s, Adj., w/act.0-10vDC, 24vAC, Elec	50	30-600	Rc 2" union F	3.06	M9108-GGA-5	0-10vDC, 24vAC, Elec	M9000-525-5	
	VP101FBD	PICV, 50mm, 3.33l/s, Adj., w/act.0-10vDC, 24vAC, Elec	50	30-400	Rc 2" union F	3.33	M9108-GGA-5	0-10vDC, 24vAC, Elec	M9000-525-5	
	VPA050-C	PICV, 50mm, 3.64l/s, Adj., w/act.0-10vDC, 24vAC, Elec	50	35-400	Flange ISO7005-2	3.64	VAP1000-24-C	0-10vDC, 24vAC, Elec		
	VPA065-C	PICV, 65mm, 5.8l/s, Adj., w/act.0-10vDC, 24vAC, Elec	65	35-400	Flange ISO7005-2	5.80	VAP1000-24-C	0-10vDC, 24vAC, Elec		
	VPA080-C	PICV, 80mm, 7.8l/s, Adj., w/act.0-10vDC, 24vAC, Elec	80	35-400	Flange ISO7005-2	7.80	VAP3000-24-C	0-10vDC, 24vAC, Elec		
VPA100-C	PICV, 100mm, 13.9l/s, Adj., w/act.0-10vDC, 24vAC, Elec	100	35-400	Flange ISO7005-2	13.90	VAP3000-24-C	0-10vDC, 24vAC, Elec			
VPA125-C	PICV, 125mm, 25l/s, Adj., w/act.0-10vDC, 24vAC, Elec	125	35-400	Flange ISO7005-2	25.00	VAP3000-24-C	0-10vDC, 24vAC, Elec			
VPA150-C	PICV, 150mm, 40.3l/s, Adj., w/act.0-10vDC, 24vAC, Elec	150	35-400	Flange ISO7005-2	40.30	VAP3000-24-C	0-10vDC, 24vAC, Elec			
DAT Modulating On-Off FCU, None Adj. Flow	VPF015L02-C	PICV, 15mm, 0.13l/s, w/act.DAT, On-Off, 24 vAC	15	20-150	Female Rp 1/2	0.13	VA-7078-21	DAT, On-Off, 24 vAC		
	VPF015L05-C	PICV, 15mm, 0.19l/s, w/act.DAT, On-Off, 24 vAC	15	20-150	Female Rp 1/2	0.19	VA-7078-21	DAT, On-Off, 24 vAC		
	VPF015L08-C	PICV, 15mm, 0.3l/s, w/act.DAT, On-Off, 24 vAC	15	20-150	Female Rp 1/2	0.30	VA-7078-21	DAT, On-Off, 24 vAC		
	VPF020L02-C	PICV, 20mm, 0.19l/s, w/act.DAT, On-Off, 24 vAC	20	20-150	Female Rp 3/4	0.19	VA-7078-21	DAT, On-Off, 24 vAC		
	VPF020L03-C	PICV, 20mm, 0.22l/s, w/act.DAT, On-Off, 24 vAC	20	20-150	Female Rp 3/4	0.22	VA-7078-21	DAT, On-Off, 24 vAC		
	VPF020L04-C	PICV, 20mm, 0.26l/s, w/act.DAT, On-Off, 24 vAC	20	20-150	Female Rp 3/4	0.26	VA-7078-21	DAT, On-Off, 24 vAC		
	VPF020L05-C	PICV, 20mm, 0.3l/s, w/act.DAT, On-Off, 24 vAC	20	20-150	Female Rp 3/4	0.30	VA-7078-21	DAT, On-Off, 24 vAC		
	VPF025L04-C	PICV, 25mm, 0.26l/s, w/act.DAT, On-Off, 24 vAC	25	20-150	Female Rp 1	0.26	VA-7078-21	DAT, On-Off, 24 vAC		
	VPF025L05-C	PICV, 25mm, 0.3l/s, w/act.DAT, On-Off, 24 vAC	25	20-150	Female Rp 1	0.30	VA-7078-21	DAT, On-Off, 24 vAC		
	VPF020H06-C	PICV, 20mm, 0.32l/s, w/act.DAT, On-Off, 24 vAC	20	30-200	Female Rp 3/4	0.32	VA-7078-21	DAT, On-Off, 24 vAC		
	VPF020H07-C	PICV, 20mm, 0.34l/s, w/act.DAT, On-Off, 24 vAC	20	30-200	Female Rp 3/4	0.34	VA-7078-21	DAT, On-Off, 24 vAC		
	VPF020H08-C	PICV, 20mm, 0.37l/s, w/act.DAT, On-Off, 24 vAC	20	30-200	Female Rp 3/4	0.37	VA-7078-21	DAT, On-Off, 24 vAC		
	VPF020H10-C	PICV, 20mm, 0.42l/s, w/act.DAT, On-Off, 24 vAC	20	30-200	Female Rp 3/4	0.42	VA-7078-21	DAT, On-Off, 24 vAC		
	VPF025H06-C	PICV, 25mm, 0.32l/s, w/act.DAT, On-Off, 24 vAC	25	30-200	Female Rp 1	0.32	VA-7078-21	DAT, On-Off, 24 vAC		
VPF025H08-C	PICV, 25mm, 0.37l/s, w/act.DAT, On-Off, 24 vAC	25	30-200	Female Rp 1	0.37	VA-7078-21	DAT, On-Off, 24 vAC			
VPF025H10-C	PICV, 25mm, 0.42l/s, w/act.DAT, On-Off, 24 vAC	25	30-200	Female Rp 1	0.42	VA-7078-21	DAT, On-Off, 24 vAC			